



SHOTKING

MAKERS OF THE
WALKER PEENIMPAC

Model S-34-55 500



The model S-34-55-500 was designed specifically for larger tanks and cylinders. This machine can handle tanks from 30" diameter to 48" diameter and has an effective cleaning width of 130". Average cycle time for this model is 10 minutes. This machine has four 10 horsepower blasting motors and can be configured with two 5 horsepower side blasting motors depending on the configuration of the part to be cleaned. Loading is simple using your forklift.

- Blasting Wheels: 4 lower wheels, 2 side wheels
- Horsepower: 10 HP lower wheels, 5 HP side wheels
- Footprint: 168in Wide x 72in Deep x 124in High
- Basket Speed: 2 RPM
- Dust Collector: (2) Model CC
- Cabinet: 1/4in thick Abrasive Resistant Alloy
- Construction: Bolt-together for easy replacement of components
- Electrical Consumption: 37.3 KWH
- Electrical: 3 phase, 230 volt or 460 volt
 - Nema 12 enclosure
 - All motors thermal overload protection
 - All motors totally enclosed fan cooled
- Safety: Blast wheels only operate if door is closed
 - Cable pull switch across machine front

(229)242-6824 • sales@shotking.com

302 South Railroad Ave. Valdosta, GA 31620 USA

www.shotking.com